

2006-08 Hyundai Azera

About the Vehicle

Make: Hyundai
Model: Azera
Year: 2006-08

OPTIONS

INFINITY SOUND SYSTEM
8 SPEAKER SYSTEM

In Dash Application

Dash Type : Double Din
Aftermarket: Single/Double Din
Kit: HY1610B/HY1620B
Harness: HY07B
Antenna Adapter: Std-ADT

AMPLIFIER LOCATIONS:

Passenger side rear quarter panel.

Wire Color Codes

+12V Constant = RED

+12v Acc. Switched = ORANGE

-12V Chassis Ground = BLACK

+12V Illumination = RED/ORANGE

+12V Dimmer = N/A

Amp Remote =

LF+ = YELLOW

LF- = BLACK

RF+ = BLUE

RF- = RED

LR+ = GREEN

LR- = ORANGE

RR+ = BROWN

RR- = WHITE



SCOSCHE®

Speaker Notes

Front

Speaker Sizes

Upper Door: 1" Tweeter
Lower Door: 6 1/2" Midrange
Speaker Adapter: TBA
Factory Assembly: Speaker Adapter built onto speaker.

NOTES

Dimensions:

W=

L=

D=

Rear

Speaker Sizes

Rear Door : 6 1/2" Midbass
Rear Quarter Panel: 8" Sub woofer
Factory Assembly: Speaker Adapter built onto Speaker.

NOTES

Dimensions:

W=

L=

D=

2006-08 Hyundai Azera

SCOSCHE®

Images

Radio Removal

1. Using a panel removal tool extract the trim panel that runs across the top have of the dash.
2. Extract (2) PHS from behind.
3. Extract (4) PHS securing factory radio

Front Speakers

Center Channel

1. Using a PRT unsnap speaker grill and remove.
2. Extract (2) PHS securing speaker, lift away, disconnect and remove

Front Door

1. Extract (2) PHS located at the door handle.
2. Extract (1) PHS located in the door release cup.
3. Using a PRT unsnap the side view mirror triangle panel.
4. Extract (1) PHS from behind panel.
5. Using a PRT unsnap prameter of door panel. Lift away, disconnect and remove.
6. Midrange 6 1/2 are riveted to door panel and speaker adapter is built into speaker.

Rear Speaker

1. Extract (2) PHS located at the door handle.
2. Extract (1) PHS located in the door release cup.
3. Extract (1) PHS located on the top inside part of the door panel closest to the door jam.
4. Using a PRT unsnap perimeter of door panel, lift away, disconnect and remove.



Front Speaker



Rear



Tweeter

1. Using steps 1-5 on the front door removal instructions remove door panel, disconnect and remove.
2. Extract (2) PHS located at the back side of the door panel.

Tweeter Removal