

2001-2003 CHEVROLET MALIBU



Year: 2001-2003

Make: Chevrolet

Model: Malibu

IN-DASH APPLICATION:

Dash Type: DIN and half

Harness: GMO6

Kit: GM1580/1583

Antenna Adapter: MDA-1

FRONT SPEAKERS:

Lower Door: 4x6" speaker with factory adapter.

When installing an aftermarket 4x6" speaker, no adapter is needed.

REAR SPEAKERS:

Rear Deck: 6x9" speaker mounted to factory metal.

When installing an aftermarket 6x9" speaker, no adapter is required. If installing an aftermarket 5 ¼" or 6 ½" speaker, we recommend the Scosche SA69 speaker adapter.

WIRE COLOR CODES: Not Available

+12V Constant =
+12V Accessory Switched =
-12V Chassis Ground =
+12V Illumination =
+12V Dimmer =
Amp Remote =
LF+ =
LF- =
RF+ =
RF- =
LR+ =
LR- =
RR+ =
RR- =

2002 Chevrolet Malibu

PRELIMINARY: Disconnect the negative battery cable.

ANTENNA: Rear passenger fender

RADIO REMOVAL AND IN-DASH INSTALLATION:

Note: The factory radio provision is for a DIN and half sized radio. Recommended kit; GM1583B

1. Remove ignition ring using small pick.
2. Using panel removal tool, pry out dash bezel, disconnect and remove.
3. Extract (3) 9/32 screws securing radio, disconnect and remove.

FRONT DOOR SPEAKER INSTALLATION:

Note: The factory speaker provision is for a 4x6" speaker in a factory adapter.

1. Extract (2) hex bolts from behind door handle.
2. Extract (1) T-15 Torx screw from behind screw cover in door opener cup.
3. Remove door opener cup by sliding forward and pull away.
4. Remove inside power mirror cover.
5. Remove window crank using windows crank removal tool, on non-power models.
6. Pry door panel out, up and away, Disconnect and remove.
7. Extract (4) 9/32 screws securing speaker, disconnect and remove.

REAR DECK SPEAKER INSTALLATION:

Note: The factory speaker provision is for a 6x9" 4-Hole speaker.

1. Remove speaker grills by prying them off with a panel removal tool.
2. Extract (4) Philips head screws securing speaker, disconnect and remove.

