

2008-10 Dodge Charger

ABOUT THE VEHICLE



Make: 2008-10

Model: Dodge

Year: Charger



Scosche App



SCOSCHE®

SPEAKER NOTES

Front Speakers:

Dash:	3 1/2"
Pillar:	TBA
Upper Door:	TBA
Lower Door:	6X9"
Speaker Adapter:	N/A
Speaker Harness:	TBA
Speaker Assembly:	TBA
Speaker Assembly:	(4) T-20 Torx Screws

Dimensions:

Dash	Door
L: 0.000	L: 6.483
W: 0.000	W: 9.280
D: 0.000	D: 3.021

Rear Speakers:

Upper Door:	TBA
Lower Door:	TBA
Rear Deck:	6X9"
Subwoofer:	10"
Speaker Adapter:	N/A
Speaker Harness:	TBA
Speaker Assembly:	(4) 7mm Screws
Speaker Assembly:	TBA

Dimensions:

Rear	Sub
L: 6.485	L: 0.000
W: 9.274	W: 0.000
D: Trunk	D: 0.000

APPLICATIONS

Dash Type:	New Custome Dash
Aftermarket Type:	Single/Double Din

Aftermaket Kits:

Aftermarket Kit:	CR1288B
Aftermarket Kit:	TBA

Harness/Interface/Adapters:

Radio Harness:	CR06SR
Antenna Adapter:	VWA3B
Blue Fusion/Bluetooth:	TBA
AUX / iPod Interface:	TBA

Other:

Auxiliary / 3.5mm:	On Radio
USB Input:	On Radio
Factory Amplifier:	TBA

FACTORY COLOR CODES

12v Battery (+):	Red/Orange
12v Accessory (+):	Data
12v Ground (-):	Black/Green
12v Amp Turn On (+):	Data
Illumination:	Data
Left Front Speaker (+):	Gray/Purple
Left Front Speaker (-):	Gray/Yellow
Right Front Speaker (+):	Green/Purple
Right Front Speaker (-):	Green/Yellow
Left Rear Speaker (+):	Green/Orange
Left Rear Speaker (-):	Green/White
Right Rear Speaker (+):	Green/Brown
Right Rear Speaker (-):	Yellow

PRELIMINARY:

Disconnect the negative battery cable.

Make: Dodge
Model: Charger
Year: 2008-10



Scosche App



RADIO



1. With Panel Removal Tool, unclip cigarette lighter Panel below A/C controls, unplug and remove.
2. With panel Removal Tool, unclip Radio/AC Panel, unplug and remove.
3. Extract (4) Phillips Head Screws securing Radio, unplug and remove.

DASH SPEAKERS



1. With Panel Removal Tool, unclip Speaker Gril and remove.
2. Extract (2) Phillips Head Screws securing Speaker, unplug and remove.

CENTER DASH SPEAKER



1. With Panel Removal Tool, unclip Speaker Gril and remove.
2. Extract (2) Phillips Head Screws securing Speaker, unplug and remove.

FRONT DOOR SPEAKERS



1. With flat head screwdriver, unclip screw cover inside door handle and extract (1) Phillips Head Screw.
2. With flat head screwdriver, unclip screw cover inside door grip handle and extract (1) Phillips Head Screw.
3. With Panel Removal Tool, unclip and remove (5) plastic screws on the outer parimeter of the door panel.
4. Extract (4) Phillips Head Screws on the lower outer parimeter of the door panel.
5. With panel Removal Tool, unclip Door Panel, unplug and remove.
6. Extract (4) T-20 Torx screws securing Speaker, unplug and remove.

PRELIMINARY:

Disconnect the negative battery cable.

Make: Dodge
Model: Charger
Year: 2008-10



REAR DECK SPEAKERS



1. Fold down back seats and extract (1) 10mm screw from left and right padded side panels.
2. With Panel Removal Tool, unclip seats padded side panels and remove.
3. Extract (2) Phillips Head Screws securing left and right lower side Panels, with Panel Removal Tool, unclip and remove.
4. Remove left and right rubber door seal, with Panel Removal Tool, unclip left and right upper side panels and remove.
5. With Panel Removal Tool, unclip (2) plastic screws securing rear deck panel and remove the rear deck panel.
6. Extract (4) 7mm screws securing Speaker, unplug and remove.

REAR DECK SUBWOOFER



1. Fold down back seats and extract (1) 10mm screw from left and right padded side panels.
2. With Panel Removal Tool, unclip seats padded side panels and remove.
3. Extract (2) Phillips Head Screws securing left and right lower side Panels, with Panel Removal Tool, unclip and remove.
4. Remove left and right rubber door seal, with Panel Removal Tool, unclip left and right upper side panels and remove.
5. With Panel Removal Tool, unclip (2) plastic screws securing rear deck panel and remove the rear deck panel.
6. Extract (4) 7mm screws securing Subwoofer, unplug and remove.

AMPLIFIER

TBA.

OTHER

TBA.