

# 2003-06 Hyundai Tiburon

## About the Vehicle

Make: Hyundai  
Model: Tiburon  
Year: 2003-06

### OPTIONS

CD Player  
6 Speaker System  
INFINITY Sound System

## In Dash Application

Dash Type: Double Din  
Aftermarket Type: Single/Double Din  
Kits: HY1604B/HY1618B  
Harness: HY04B  
Antenna Adapter: Std. Motorola

### AMPLIFIER LOCATIONS:

VEHICLE MAYBE EQUIPPED WITH FACTORY AMP  
LOCATED ON DRIVER SIDE PANEL ON FRONT OF REAR  
SPEAKER.

## Wire Color Codes

+12V Constant = RED

+12v Acc. Switched = YELLOW

-12V Chassis Ground = BLACK

+12V Illumination = N/A

+12V Dimmer = PINK/BLACK

Amp Remote = N/A

LF+ = WHITE

LF- = BROWN

RF+ = BLACK

RF- = YELLOW

LR+ = BLUE

LR- = RED

RR+ = GREEN

RR- = ORANGE



## SCOSCHE®

## Speaker Notes

### Front

### Speaker Sizes

Upper Door: 1" Tweeter  
Lower Door: 5 1/4" Midrange  
Factory ASsembly: (4) Phillips Head screws securing speaker.

### NOTES

Tweeter located on the inner mirror cover.

### Dimensions:

W= 5 3/4"

L= 5 3/4"

D= 1 3/4"

### Rear

### Speaker Sizes

Rear Side Panels : 6X9" Midbass  
Factory Assembly: (3) Phillips Head screws securing speaker.

### NOTES

The vehicle may also be equipped with a factory 10" subwoofer which would be located on the driver side quarter panel inside the trunk.

### Dimensions:

W= 8 3/4"

L= 5 3/4"

D= 5 1/2"

# 2003-06 Hyundai Tiburon

SCOSCHE®

## Images

### Radio



### Front Speaker



### Rears



### Radio Removal

1. Using panel removal tool pry out radio bezel, disconnect and remove.
2. Extract (4) PHS screws securing radio, disconnect and remove.

### Front Speaker

1. Using a panel removal tool pop off tweeter cover. Disconnect and remove.
2. At back of door pop off (3) screws covers and extract (3) PHS.
3. Extract (1) PHS screw from door opener cavity
4. Using panel removal tool pop off cover on door handle. Extract (2) PHS from behind.
5. Extract (1) PHS from door opener panel and remove.
6. Pop out and pull up on door panel. Disconnect and remove.
7. Extract (4) PHS from speaker disconnect and remove.

### Rear Speaker

1. Using panel removal tool pop out (2) snaps on running board. Pop out and remove.
2. Using 14mm socket remove (2) seat belts bolts from running board area.
3. Using PHS driver. Remove (1) screw on side panel next to speaker grill.
4. Using 12mm socket remove (2) bolts in between top and bottom rest of back seat.
5. Push (2) black clips at front bottom edge of bottom rest of back seat and pull up on seat to remove.
6. behind backseat UN screw plastic bolt that holds luggage net.
7. remove (1) 10mm bolt at top of subwoofer enclosure. Pop off panel behind seat that holds luggage net.
8. using panel removal tool. Pop out rear side panel and remove.
9. extract (3) T15 torx screws from speaker. Disconnect and remove.