

**2001
SAAB
9-5**



Year: 2001 Make: Saab Model: 9-5

IN-DASH APPLICATION:

Dash Type: DinandHalf Kit: N/A Harness: N/A

FRONT SPEAKERS:

Dash Speakers: 3 ½" speakers mounted in dash

Door Speakers: 6 ½" 4-Hole Pin Cushion speaker mounted in a factory speaker adapter

REAR SPEAKERS:

Door Speakers: 2 ½" 4-Hole Pin Cushion speaker mounted to a factory speaker adapter.

WIRE COLOR CODES:

+12V Constant = Red
+12V Accessory Switched = Red/Blue
-12V Chassis Ground = Black
+12V Illumination =
+12V Dimmer =
Power Antenna = Green
Amp Remote =
 LF+ = Red
 LF- = Blue
 RF+ = Blue/White
 RF- = Red/White
 LR+ = Grey
 LR- = Brown/Red
 RR+ = Yellow/White
 RR- = Orange/White

**2001 Saab 95
Sedan**

PRELIMINARY: Disconnect the negative battery cable.

ANTENNA: Rear window.

RADIO REMOVAL AND IN-DASH INSTALLATION:

Note: The factory radio provision is for a Double DIN sized radio.

1. Use DT-1* radio removal tools. To remove the radio insert tools in access holes, pull outwards, then slide radio out of cage. *DT-1 can be purchased from Scosche or a Ford dealer.

FRONT DASH SPEAKERS

Note: The factory speaker provision is for a 3 1/2" 2 hole standard mounted speaker.

1. Using panel removal tool, carefully pry out speaker grill.
2. Extract (2) t25 Torx securing speaker, Disconnect and remove.

FRONT DOOR SPEAKER INSTALLATION:

Note: The factory speaker provision is for a 6-1/2" 4-Hole Pincushion speaker mounted to a factory speaker adapter.

1. Carefully pull out upper doorframe cover.
2. Remove screw covers on handles to expose all three t-30 Bolts.
3. Pull forward and unhitch handle.
4. Push in and pull out plastic fastener.
5. Pry off light by starting at the front of the light cover.
6. Carefully pry off door panel.
7. Remove (3) Phillips head screws.

REAR DOOR SPEAKER INSTALLATION:

Note: The factory speaker provision is for a 2" Pincushion speaker mounted directly to metal.

1. Carefully pry off upper doorframe cover.
2. Extract (1) T-30 Torx from under screw cover in door opener cup.
3. Extract (2) T-30 Torx from under screw cover in door handle.
4. Pry door panel out using panel removal tool, disconnect and remove panel.
5. Extract (2) Philips Head screw securing speaker, disconnect and remove.

REAR DECK SPEAKER INSTALLATION:

Note: The factory speaker provision is for a 6" x 9" Pincushion speaker mounted directly to metal.

1. Fold down rear seats.
2. Push in and pry out plastic fasteners.
3. Pry up on front of grill to dislodge metal clips.
4. Slide grill assembly forward.
5. Remove (4) T-25 Torx bolts holding speaker in.

