


# SCOSCHE®

## 1973 - 87 CHEVROLET/GMC KIT

GM1481



### CHEVROLET

1973 - 87 BLAZER FULLSIZE  
1973 - 87 PICKUP FULLSIZE  
1973 - 87 SUBURBAN

### GMC

1973 - 87 JIMMY  
1973 - 87 PICKUP FULLSIZE  
1973 - 87 SUBURBAN

### INTRODUCTION / PRELIMINARY

Thank you for purchasing the Scosche GM1481 Kit. This Kit was manufactured with the highest of quality standards.

#### NOTES:

See your vehicle's instructions for any special tool your installation might require. Read all instructions accompanying your car stereo for proper wiring and mounting instructions.

### STEREO INSTALLATION

1. Remove (1) Screw from central air conditioning duct directly below radio. Push duct right then left to remove.
2. Remove knobs and shafts nuts from radio.
3. Remove (1) hex nut securing radio rear support under dash.
4. Disconnect power, antenna, speaker and all electrical connections. Remove radio

### FACTORY WIRING CODES

For Factory Wiring Codes go to: [www.scosche-cars.com](http://www.scosche-cars.com) or Call

#### LIABILITY DISCLAIMER

This instruction booklet is based on carefully documented data and research of automobile dash disassembly, wire harness/codes and information pertaining to installation of this kit (GM1481) in 1973-87 General Motors Vehicles. Scosche Industries, Inc. can not be held responsible for discrepancies/inconsistencies that may occur due to the automobile manufacturing changes or options, or damage that may occur in the automobile during the installation of components while using this booklet.

If you have any further questions, call our toll free technical help line at: **1-800-621-3695x3**


© 2003 SCOSCHE INDUSTRIES, INC.

SI 12/03 - GM1481 (3000003)

# SCOSCHE®

## 1973 - 87 CHEVROLET/GMC KIT

GM1481



### CHEVROLET

1973 - 87 BLAZER FULLSIZE  
1973 - 87 PICKUP FULLSIZE  
1973 - 87 SUBURBAN

### GMC

1973 - 87 JIMMY  
1973 - 87 PICKUP FULLSIZE  
1973 - 87 SUBURBAN

### INTRODUCTION / PRELIMINARY

Thank you for purchasing the Scosche GM1481 Kit. This Kit was manufactured with the highest of quality standards.

#### NOTES:

See your vehicle's instructions for any special tool your installation might require. Read all instructions accompanying your car stereo for proper wiring and mounting instructions.

### STEREO INSTALLATION

1. Remove (1) Screw from central air conditioning duct directly below radio. Push duct right then left to remove.
2. Remove knobs and shafts nuts from radio.
3. Remove (1) hex nut securing radio rear support under dash.
4. Disconnect power, antenna, speaker and all electrical connections. Remove radio

### FACTORY WIRING CODES

For Factory Wiring Codes go to: [www.scosche-cars.com](http://www.scosche-cars.com) or Call

#### LIABILITY DISCLAIMER

This instruction booklet is based on carefully documented data and research of automobile dash disassembly, wire harness/codes and information pertaining to installation of this kit (GM1481) in 1973-87 General Motors Vehicles. Scosche Industries, Inc. can not be held responsible for discrepancies/inconsistencies that may occur due to the automobile manufacturing changes or options, or damage that may occur in the automobile during the installation of components while using this booklet.

If you have any further questions, call our toll free technical help line at: **1-800-621-3695x3**

© 2003 SCOSCHE INDUSTRIES, INC.

SI 12/03 - GM1481 (3000003)